

- University of Mining & Technology*, vol. 42, no. 6, pp. 975-981, 2013.
- [13] Barth W., "Flow patterns during the conveyance of solid particles and droplets in gases," *Chem. Ing. Tech*, vol. 30, pp. 171-180, 1958.
- [14] Mo X., Cai R., Huang X., et al., "The effects of wall friction and solid acceleration on the mal-distribution of gas-solid flow in double identical parallel cyclones," *Powder Technology*, vol. 286, pp. 471-477, 2015. DOI: [10.1016/j.powtec.2015.08.017](https://doi.org/10.1016/j.powtec.2015.08.017).
- [15] Chu K. W., Kuang S. B., Yu A. B., et al., "Particle scale modelling of the multiphase flow in a dense medium cyclone: Effect of fluctuation of solids flowrate," *Minerals Engineering*, vol. 33, pp. 34-45, 2012. DOI: [10.1016/j.mineng.2011.12.011](https://doi.org/10.1016/j.mineng.2011.12.011).
- [16] Qian F., Zhang J., Zhang M., "Effects of the prolonged vertical tube on the separation performance of a cyclone," *Journal of hazardous Materials*, vol. 136, no. 3, pp. 822-829, 2006. DOI: [10.1016/j.jhazmat.2006.01.028](https://doi.org/10.1016/j.jhazmat.2006.01.028).
- [17] Pourmahmoud N., Esmaily R. and Hassanzadeh A., "CFD investigation of vortex tube length effect as a designing criterion," *International Journal of Heat & Technology*, vol. 33, no. 1, pp. 129-136, 2015. DOI: [10.18280/ijht.330118](https://doi.org/10.18280/ijht.330118).
- [18] Bounaouara H., Ettouati H., Ticha H. B., et al., "Numerical simulation of gas-particles two phase flow in pipe of complex geometry: pneumatic conveying of olive cake particles toward a dust burner," *International Journal of Heat and Technology*, vol. 33, no. 1, pp. 99-106, 2015. DOI: [10.18280/ijht.330114](https://doi.org/10.18280/ijht.330114).
- [19] Li S., Liu D. and Li Q. "The optimal design of a wind tunnel model sting system based on the CFD method," *International Journal of Heat & Technology*, vol. 33, no. 4, pp. 137-144, 2015. DOI: [10.18280/ijht.330417](https://doi.org/10.18280/ijht.330417).