

Environment, Vol. 45, pp. 1521-1528. DOI: [10.1016/j.buildenv.2010.01.003](https://doi.org/10.1016/j.buildenv.2010.01.003)

- [7] Delfani S., Esmaeelian J., Pasdarsahri H., Karami M. (2010). Energy saving potential of an indirect evaporative cooler as a pre-cooling unit for mechanical cooling systems in Iran, *Energy and Buildings*, Vol. 42, pp. 2169-2176. DOI: [10.1016/j.enbuild.2010.07.009](https://doi.org/10.1016/j.enbuild.2010.07.009)
- [8] De Angelis A., Ceccotti L., Saro O. (2016). Cooling energy savings with dry-cooler equipped plants in office buildings, *International Journal of Heat and Technology*, Vol. 34, Special Issue 2, pp. S205-S211. DOI: [10.18280/ijht.34S203](https://doi.org/10.18280/ijht.34S203)
- [9] 2009 ASHRAE Handbook of Fundamentals (SI).
- [10] ISO 7730 Ergonomics of the thermal environment - Analytical determination and interpretation of thermal comfort using calculation of the PMV and PPD indices and local thermal comfort criteria, 2005.

NOMENCLATURE

EER	energy efficiency ratio
H	number of hours, h
U	thermal transmittance, W. m ⁻² . K ⁻¹
θ	temperature

Subscripts

c	chilled
C	chiller
e	external
w	window
out	outlet