

- imagery EEG using wavelet transform. *Journal of Biomedical Science and Engineering*, 1(01): 64.
- [26] Li, M.A., Zhu, W., Liu, H.N., Yang, J.F. (2017). Adaptive feature extraction of motor imagery EEG with optimal wavelet packets and SE-isomap. *Applied Sciences*, 7(4): 390. <https://doi.org/10.3390/app7040390>
- [27] www.gtec.at (accessed on 1.09.2018).
- [28] McFarland, D.J., Miner, L.A., Vaughan, T.M., Wolpaw, J.R. (2000). Mu and beta rhythm topographies during motor imagery and actual movements. *Brain topography*, 12(3): 177-186.
- [29] Osman, A., Robert, A. (2001). Time-course of cortical activation during overt and imagined movements. *Proc. Cognitive Neuroscience Annu. Meet. New York*, 1: 1842-1852.
- [30] Fraga, F.J., Falk, T.H., Kanda, P.A., Anghinah, R. (2013). Characterizing Alzheimer's disease severity via resting-awake EEG amplitude modulation analysis. *PLoS One*, 8(8): e72240. <https://doi.org/10.1371/journal.pone.0072240>
- [31] Fraga, F.J., Falk, T.H., Trambaiolli, L.R., Oliveira, E.F., Pinaya, W.H., Kanda, P.A., Anghinah, R. (2013). Towards an EEG-based biomarker for Alzheimer's disease: Improving amplitude modulation analysis features. *ICASSP*, 1207-1211. <https://doi.org/10.1109/ICASSP.2013.6637842>
- [32] Lee, F., Scherer, R., Leeb, R., Neuper, C., Bischof, H., Pfurtscheller, G. (2005). A comparative analysis of multi-class EEG classification for brain computer interface. In *Proceedings of the 10th Computer Vision Winter Workshop*, pp. 195-204.
- [33] Martisius, I., Damasevicius, R., Jusas, V., Birvinskas, D. (2012). Using Higher Order Nonlinear Operators for SVM Classification of EEG Data. *Elektronika Ir Elektrotechnika*, 119(3): 99-102. <http://dx.doi.org/10.5755/j01.eee.119.3.1373>
- [34] Lotte, F., Bougrain, L., Cichocki, A., Clerc, M., Congedo, M., Rakotomamonjy, A., Yger, F. (2018). A review of classification algorithms for EEG-based brain-computer interfaces: A 10 year update. *Journal of Neural Engineering*, 15(3): 031005. <https://doi.org/10.1088/1741-2552/aab2f2>
- [35] Resalat, S.N., Saba, V. (2016). A Study of Various Feature Extraction Methods on a Motor Imagery Based Brain Computer Interface System, *Basic Clin Neurosci.*, 7(1): 13-19.
- [36] Barreto, G.A., Frota, R.A., de Medeiros, F.N. (2004). On the classification of mental tasks: A performance comparison of neural and statistical approaches. In *Machine Learning for Signal Processing, Proceedings of the 14th IEEE Signal Processing Society Workshop*, pp. 529-538. <https://doi.org/10.1109/MLSP.2004.1423016>
- [37] Babiloni, F., Bianchi, L., Semeraro, F., del R Millan, J., Mourino, J., Cattini, A., Salinari, S., Marciani, M.G., Cincotti, F. (2001). Mahalanobis distance-based classifiers are able to recognize EEG patterns by using few EEG electrodes. *Engineering in Medicine and Biology Society, Proceedings of the 23rd Annual International Conference of the IEEE*, 1. <https://doi.org/10.1109/IEMBS.2001.1019019>
- [38] Eva, O.D., Lazar, A.M. (2018). An Amplitude Modulation of Cerebral Rhythms based Method in a Motor Task BCI Paradigm. *IJACSA*, 9(9): 26-31. <https://doi.org/10.14569/IJACSA.2018.090904>
- [39] Ince, N.F., Tewfik, A.H., Arica, S. (2007). Extraction subject-specific motor imagery time-frequency patterns for single trial EEG classification. *Computers in Biology and Medicine*, 37(4): 499-508. <https://doi.org/10.1016/j.combiomed.2006.08.014>
- [40] Shan, H., Xu, H., Zhu, S., He, B. (2015). A novel channel selection method for optimal classification in different motor imagery BCI paradigms. *Biomedical Engineering Online*, 14(1): 93. <https://doi.org/10.1186/s12938-015-0087-4>
- [41] Tu W., Sun S. (2012). Dynamical ensemble learning with model-friendly classifiers for domain adaptation. *Proceedings of the 21st International Conference on Pattern Recognition (ICPR)*, pp. 1181-1184.