

















- concavity, straightness and roughness in milling process. *Material Today Proceedings*, Elsevier, 5(2): 5296-5302. <https://doi.org/10.1016/j.matpr.2017.12.113>
- [20] Dahbi, S., Ezzine, L., Moussami, H.E.L. (2017). Modeling of cutting performances in turning process using artificial neural networks. *International Journal of Engineering Business Management*, 9: 1-13. <https://doi.org/10.1177%2F1847979017718988>
- [21] Das, D., Chaubey, A., Nayak, B.B., Mishra, P.C., Samal, C. (2018). Investigation on cutting tool wear in turning AI 7075/SiCp metal matrix composites. *International Conference on Mechanical, Materials and Renewable Energy*, 377: 1-7. <https://doi.org/10.1088/1757-899X/377/1/012110>
- [22] Qu, J., Shih, A.J. (2003). Analytical surface roughness parameters of a theoretical profile consisting of elliptical arcs. *Machining Science and Technology: An International Journal*, 7(2): 281-294. <https://doi.org/10.1081/MST-120022782>
- [23] Shaban, Y., Yacout, S., Balazinski, M., Jemielniak, K. (2017). Cutting tool wear detection using multiclass logical analysis of data. *Machining Science and Technology*, 21(4): 526-541. <https://doi.org/10.1080/10910344.2017.1336177>
- [24] Sheikh-Ahmad, J., Twomey, J., Kalla, D., Lodhia, P. (2007). Multiple regression and committee neural network force prediction models in milling FRP. *Machining Science and Technology: An International Journal*, 11(3): 391-412.
- [25] Pendse, D.M., Joshi, S.S. (2004). Modeling and optimization of machining process in discontinuously reinforced aluminums matrix composites. *Machining Science and Technology*, 8(1): 85-102. <https://doi.org/10.1081/MST-120034242>
- [26] Khataee, A.R., Kasiri, M.B. (2010). Artificial neural networks modeling of contaminated water treatment processes by homogeneous and heterogeneous nanocatalysis. *Journal of Molecular Catalysis A: Chemical*, 331(2010): 86-100. <https://doi.org/10.1016/j.molcata.2010.07.016>
- [27] Nowruzi, H., Ghassemi, H. (2016). Using artificial neural network to predict velocity of sound in liquid water as a function of ambient temperature, electrical and magnetic fields. *Journal of Ocean Engineering and Science*, 1(3): 203-211. <https://doi.org/10.1016/j.joes.2016.07.001>
- [28] Munoz-Escalona, P., Maropoulos, P.G. (2014). A geometrical model for surface roughness prediction when face milling Al 7075-T7351 with square insert tools. *Journal of Manufacturing Systems*, Elsevier, 36: 216-223. <https://doi.org/10.1016/j.jmsy.2014.06.011>
- [29] Cus, F., Zuperl, U., Gecevska, V. (2007). High speed end-milling optimization using particle swarm intelligence. *Journals of Achievements in Materials and Manufacturing Engineering*, 2(22): 75-78.
- [30] Wang, Z.R., Zou, Y.F., Zhang, F. (2011). A machine vision approach to tool wear monitoring based on the image of workpiece surface texture. *Advanced Materials Research*, (154-155): 412-416. <https://doi.org/10.4028/www.scientific.net/AMR.154-155.412>