joining NOMA with multicast CR organizing, further execution enhancement as far as high productivity can be accomplished. The proposed handoff method means to reduce the SU (Secondary User) handoff delay brought about by spectrum handoff. In this paper we consider the impacts of other divert conditions in perspective of packet error rate (PER). To upgrade the nature of administration applications, it is imperative to consider both the handoff delay and the transmission channel quality, while picking channels for spectrum handoff. The outcomes assessment dependent by and large holding up of all SU associations and all out administration time of all PU association.

REFERENCES

[1] Liao Y, Song L, Han Z, Li Y. (2015). Full duplex cognitive radio: A new design paradigm for enhancing spectrum usage. IEEE Communications Magazine 53(5): 138-45. https://doi.org/10.1109/MCOM.2015.7105652

[2] Arafat AO, Al-Hourani A, Nafi NS, Gregory MA. (2017). A survey on dynamic spectrum access for LTE-advanced. Wireless Personal Communications 97(3): 3921-41. https://doi.org/10.1007/s11277-017-4707-0

[3] Hawa M, AlAmmouri A, Alhiary A, Alhamad N. (2017). Distributed opportunistic spectrum sharing in cognitive radio networks. International Journal of Communication Systems 30(7): 20-25. https://doi.org/10.1002/dac.3147

[4] Raschellà A, Umbert A. (2016). Implementation of cognitive radio networks to evaluate spectrum management strategies in real-time. Computer Communications 79: 37-52. https://doi.org/10.1016/j.comcom.2015.11.009

[5] Kumar R, Darak SJ, Sharma AK, Tripathi R. (2016). Two-stage decision making policy for opportunistic spectrum access and validation on USRP testbed. Wireless Networks 1-5. https://doi.org/10.1007/s11276-016-1420-y

[6] Pérez-Romero J, Raschellà A, Sallent O, Umbert A. (2016). A belief-based decision-making framework for spectrum selection in cognitive radio networks. IEEE Transactions on Vehicular Technology 65(10): 8283-96. https://doi.org/10.1109/TVT.2015.2508646

[7] Jia M, Liu X, Gu X, Guo Q. (2017). Joint cooperative spectrum sensing and channel selection optimization for satellite communication systems based on cognitive radio. International Journal of Satellite Communications and Networking 35(2): 139-50. https://doi.org/10.1002/sat.1169

[8] Hassan MR, Karmakar GC, Kamruzzaman J, Srinivasan B. (2017). Exclusive use spectrum access trading models in cognitive radio networks: A survey. IEEE Communications Surveys & Tutorials 19(4): 2192-231. https://doi.org/10.1109/COMST.2017.2725960

[9] Kumar K, Prakash A, Tripathi R. (2016). Spectrum handoff in cognitive radio networks: A classification and comprehensive survey. Journal of Network and Computer Applications 61: 161-88. https://doi.org/10.1016/j.jnca.2015.10.008

[10] Chen YS, Cho CH, You I, Chao HC. (2011). A cross-layer protocol of spectrum mobility and handover in cognitive LTE networks. Simulation Modelling Practice and Theory 19(8): 1723-44. https://doi.org/10.1016/j.simpat.2010.09.007

[11] Dixit S, Periyalwar S, Yanikomeroglu H. (2013). Secondary user access in LTE architecture based on a base-station-centric framework with dynamic pricing. IEEE Transactions on Vehicular Technology 62(1): 284-96. https://doi.org/10.1109/TVT.2012.2221753

[12] Ramzan MR, Nawaz N, Ahmed A, Naeem M, Iqbal M, Anpalagan A. (2017). Multi-objective optimization for spectrum sharing in cognitive radio networks: A review. Pervasive and Mobile Computing 41: 106-31. https://doi.org/10.1016/j.pmcj.2017.07.010

[13] Mohamedou A, Sali A, Ali B, Othman M, Mohamad H. (2017). Bayesian inference and fuzzy inference for spectrum sensing order in cognitive radio networks. Transactions on Emerging Telecommunications Technologies 28(1): 12-15. https://doi.org/10.1002/ett.2916

[14] El Tanab M, Hamouda W. (2017). Resource allocation for underlay cognitive radio networks: A survey. IEEE Communications Surveys & Tutorials 19(2): 1249-76. https://doi.org/10.1109/COMST.2016.2631079

[15] Park JS, Yoon H, Jang BJ. (2016). SDR-based frequency interference analysis test-bed considering time domain characteristics of interferer. Advanced Communication Technology (ICACT) 517-521. https://doi.org/10.1109/ICACT.2016.7423453

[16] Castro-Hernandez D, Paranjape R. (2017). Optimization of handover parameters for LTE/LTE-A in-building systems. IEEE Transactions on Vehicular Technology. 5260–5273. https://doi.org/10.1109/TVT.2017.2711582

[17] Won SH, Cho S, Shin J. (2017). Virtual antenna mapping MIMO techniques in a massive MIMO test-bed for backward compatible LTE mobile systems. Advanced Communication Technology (ICACT) 971-978. https://doi.org/10.23919/ICACT.2017.7890253

[18] Malkowsky S, Vieira J, Liu L, Harris P, Nieman K, Kundargi N, Wong IC, Tufvesson F, Öwall V, Edfors O. (2017). The world's first real-time testbed for massive MIMO: Design, implementation, and validation. IEEE Access 5: 9073-88. https://doi.org/10.1109/ACCESS.2017.2705561

[19] Joseph SD, Manoj S, Waghmare C, Nandakumar K, Kothari A. (2017). UWB sensing antenna, reconfigurable transceiver and reconfigurable antenna based cognitive radio test bed. Wireless Personal Communications 96(3): 3435-62. https://doi.org/10.1007/s11277-017-4117-3

[20] Alam M, Trapps P, Mumtaz S, Rodriguez J. (2017). Context-aware cooperative test bed for energy analysis in beyond 4G networks. Telecommunication Systems. 64(2): 225-44. https://doi.org/10.1007/s11235-016-0171-5

[21] Marojevic V, Nealy R, Reed JH. (2017). LTE spectrum sharing research testbed: integrated hardware, software, network and data. arXiv preprint arXiv:1710.02571. https://doi.org/10.1145/3131473.3131484

[22] Hematian A, Nguyen J, Lu C, Yu W, Ku D. (2017). Software defined radio testbed setup and experimentation. In Proceedings of the International Conference on Research in Adaptive and Convergent Systems Sep 20, pp. 172-177. https://doi.org/10.1145/3129676.3129690