

- Chen, J.J. (2014). A hybrid approach for scalable subtree anonymization over big data using MapReduce on cloud. *J. Comput. Syst. Sci.*, 80(5): 1008-1020. <https://doi.org/10.1016/j.jcss.2014.02.007>
- [17] Li, Y.P., Chen, M.H., Li, Q.W., Zhang, W. (2012). Enabling multilevel trust in privacy preserving data mining. *IEEE Trans. Knowl. Data Eng.*, 24(9): 1589-1612. <https://doi.org/10.1109/TKDE.2011.124>
- [18] Wu, Y.H., Chiang, C.M., Chen, A.L.P. (2007). Hiding sensitive association rules with limited side effects. *IEEE Trans. Knowl. Data Eng.*, 19(1): 29-42. <https://doi.org/10.1109/TKDE.2007.250583>
- [19] Gkoulalas-Divanis, A., Verykios, V.S. (2009). Exact knowledge hiding through database extension. *IEEE Trans. Knowl. Data Eng.*, 21(5): 699-713. <https://doi.org/10.1109/TKDE.2008.199>
- [20] Le, H.Q., Arch-int, S., Nguyen, H.X., Arch-int, N. (2013). Association rule hiding in risk management for retail supply chain collaboration. *Computers in Industry*, 64(4): 776-784. <https://doi.org/10.1016/j.compind.2013.04.011>
- [21] Li, Y.C., Yeh, J.S., Chang, C.C. (2007). MCIF: An effective sanitization algorithm for hiding sensitive patterns on data mining. *Advanced Engineering Informatics*, 21(3): 269-280. <https://doi.org/10.1016/j.aei.2006.12.003>
- [22] Bettahally, N.K., Durga, T., Bhavani, K.E. (2012). Hiding co-occurring prioritized sensitive patterns over distributed progressive sequential data streams. *J. Netw. Comput. Appl.*, 35(3): 1116-1129. <https://doi.org/10.1016/j.jnca.2011.12.011>
- [23] Philip Chen, C.L.C., Zhang, C.Y. (2014). Data-intensive applications, challenges, techniques and technologies: A survey on big data. *Information Sciences*, 275: 314-347. <https://doi.org/10.1016/j.ins.2014.01.015>
- [24] Wu, X.D., Zhu, X.Q., Wu, G.Q., Ding W. (2014). Data mining with big data. *IEEE Trans. Knowl. Data Eng.*, 26(1): 97-107. <https://doi.org/10.1109/TKDE.2013.109>
- [25] Mehmet, E.N., Muhammed, Z.G. (2014). Hybrid K-anonymity. *Comput. Secur.*, 44: 51-63. <https://doi.org/10.1109/APSCC.2008.65>
- [26] Li, B.D., Erdin, E., Gunes, M.H., Bebis, G., Shipley, T. (2013). An overview of anonymity technology usage. *Comput. Commun.*, 36(12): 1269-1283. <https://doi.org/10.1016/j.comcom.2013.04.009>
- [27] Kisilevich, S., Rokach, L., Elovici, Y., Shapira, B. (2010). Efficient multidimensional suppression for K-anonymity. *IEEE Trans. Knowl. Data Eng.*, 22(3): 334-347. <https://doi.org/10.1109/TKDE.2009.91>
- [28] Zhang, G.F., Yun, Y., Liu, X., Chen, J.J. (2012). A time-series pattern based noise generation strategy for privacy protection in cloud computing. *Int. Symp Cluster, Cloud and Grid Computing (CCGrid)*, Ottawa, Canada. pp. 458-465. <https://doi.org/10.1109/CCGrid.2012.82>
- [29] Wang, H. (2013). Quality measurement for association rule hiding. *AASRI Procedia*, 5: 228-234. <https://doi.org/10.1016/j.aasri.2013.10.083>
- [30] George, V.M., Vassilios, S.V. (2008). A MaxMin approach for hiding frequent item sets. *Data Knowl. Eng.*, 65(1): 75-89. <https://doi.org/10.1016/j.datak.2007.06.012>
- [31] Wang, S.L., Parikh, B., Jafari, A. (2007). Hiding informative association rule sets. *Expert Syst. Appl.*, 33(2): 316-323. <https://doi.org/10.1016/j.eswa.2006.05.022>
- [32] Dasseni, E., Verkios, V.S., Elmagarmid, A.K., Bertino, E. (2001). Hiding association rules by using confidence and support. *Inf. Hiding Lect. Notes Comput. Sci.*, pp. 369-383. http://dx.doi.org/10.1007/3-540-45496-9_27