

- properties. *Applied Energy* 136: 217-227. <https://doi.org/10.1016/j.apenergy.2014.09.047>
- [20] Moghaddam MK, Mortazavi SM, Khaymian T. (2015). Micro/nano-encapsulation of a phase change material by coaxial electrospray method. *Iranian Polymer Journal* 24(9): 759-774. <https://doi.org/10.1007/s13726-015-0364-x>
- [21] Min X, Fang M, Huang Z, Liu Y, Huang Y, Wen R, Qian T, Wu X. (2015). Enhanced thermal properties of novel shape-stabilized PEG composite phase change materials with radial mesoporous silica sphere for thermal energy storage. *Scientific Reports* 5: 12964. <https://doi.org/10.1038/srep12964>
- [22] Liu C, Rao Z, Zhao J, Huo Y, Li Y. (2015). Review on nanoencapsulated phase change materials: Preparation, characterization and heat transfer enhancement. *Nano Energy* 13: 814-826. <https://doi.org/10.1016/j.nanoen.2015.02.016>
- [23] Sari A, Alkan C, Kahraman Döğüşcü D, Biçer A. (2014). Micro/nano-encapsulated n-heptadecane with polystyrene shell for latent heat thermal energy storage. *Solar Energy Materials and Solar Cells* 126: 42-50. <https://doi.org/10.1016/j.solmat.2014.03.023>
- [24] Fang G, Chen Z, Li H. (2010). Synthesis and properties of microencapsulated paraffin composites with SiO₂ shell as thermal energy storage materials. *Chemical Engineering Journal* 163(1-2): 154-159. <https://doi.org/10.1016/j.cej.2010.07.054>
- [25] De Matteis V, Cannavale A, Coppola A, Fiorito F. (2017). Nanomaterials and smart nanodevices for modular dry constructions: The project “easy House,”. *Procedia Engineering* 180: 704-714. <https://doi.org/10.1016/j.proeng.2017.04.230>
- [26] Chan WT, Liu CC, Chiau JSC, Tsai ST, Liang CK, Cheng ML, Lee HC, Yeung CY, Hou SY. (2017). In vivo toxicologic study of larger silica nanoparticles in mice. *International Journal of Nanomedicine* 12: 3421-3432. <https://doi.org/10.2147/IJN.S126823>
- [27] Finnie KS, Jacques DA, McGann MJ, Blackford MG, Barbé CJ. (2006). Encapsulation and controlled release of biomolecules from silica microparticles. *Journal of Materials Chemistry* 16: 4494-4498. <https://doi.org/10.1039/b611840b>
- [28] Zhang H, Wang X, Wu D. (2010). Silica encapsulation of n-octadecane via sol-gel process: A novel microencapsulated phase-change material with enhanced thermal conductivity and performance. *Journal of Colloid and Interface Science* 343(1): 246-255. <https://doi.org/10.1016/j.jcis.2009.11.036>
- [29] Belessiotis GV, Papadokostaki KG, Favvas EP, Efthimiadou EK, Karellas S. (2018). Preparation and investigation of distinct and shape stable paraffin/SiO₂ composite PCM nanospheres. *Energy Conversion and Management* 168: 382-394. <https://doi.org/10.1016/j.enconman.2018.04.059>
- [30] Latibari ST, Mehrali M, Mehrali M, Mahlia TMI, Metselaar HSC. (2013). Synthesis, characterization and thermal properties of nanoencapsulated phase change materials via sol-gel method. *Energy* 61: 664-672. <https://doi.org/10.1016/j.energy.2013.09.012>
- [31] Kosny J, Shukla N, Fallahi A. (2013). Cost analysis of simple phase change material-enhanced building envelopes in Southern U.S. climates. *National Renewable Energy Laboratory (U.S.)*. <https://doi.org/10.2172/1067934>
- [32] Turecek PL, Bossard MJ, Schoetens F, Ivens IA. (2016). PEGylation of Biopharmaceuticals: A review of chemistry and nonclinical safety information of approved drugs. *Journal of Pharmaceutical Sciences* 105(2): 460-475. <https://doi.org/10.1016/j.xphs.2015.11.015>
- [33] Knop K, Hoogenboom R, Fischer D. (2010). U.S. Schubert, Poly(ethylene glycol) in drug delivery: Pros and cons as well as potential alternatives. *Angewandte Chemie (International ed. in English)* 49(36): 6288-6308. <https://doi.org/10.1002/anie.200902672>
- [34] De Matteis V, Cannavale A, Martellotta F, Rinaldi R, Calcagnile P, Ferrari F, Ayr U, Fiorito F. (2019). Energy & buildings nano-encapsulation of phase change materials: From design to thermal performance, simulations and toxicological assessment. *Energy Buildings* 188-189: 1-11. <https://doi.org/10.1016/j.enbuild.2019.02.004>
- [35] Carlucci S, Bai L, De Dear R, Yang L. (2018). Review of adaptive thermal comfort models in built environmental regulatory documents. *Building and Environment* 137: 73-89. <https://doi.org/10.1016/j.buildenv.2018.03.053>
- [36] Stober W, Fink A. (1968). Controlled growth of monodispersed silica spheres in the micron size range. *Journal of Colloid and Interface Science* 26(1): 62-69. [https://doi.org/10.1016/0021-9797\(68\)90272-5](https://doi.org/10.1016/0021-9797(68)90272-5)