











- and power. Part I: An MILP based spatial optimization methodology. *Energy Conversion and Management*, 83: 347-361.  
<https://doi.org/10.1016/j.enconman.2014.03.050>
- [16] Jayasekara, S., Halgamuge, S.K., Attalage, R.A., Rajarathne, R. (2014). Optimum sizing and tracking of combined cooling heating and power systems for bulk energy consumers. *Applied Energy*, 118: 124-134.  
<https://doi.org/10.1016/j.apenergy.2013.12.040>
- [17] Wang, J.J., Fu, C., Yang, K., Zhang, X.T., Shi, G.H., Zha, J. (2013). Reliability and availability analysis of redundant BCHP (building cooling, heating and power) system. *Energy*, 61(1): 531-540.  
<https://doi.org/10.1016/j.energy.2013.09.018>
- [18] Sun, G.X., Bin, S. (2017). Router-level internet topology evolution model based on multi-subnet composited complex network model. *Journal of Internet Technology*, 18(6): 1275-1283.  
<http://dx.doi.org/10.6138/JIT.2017.18.6.20140617>
- [19] Rohaninejad, M., Kheirkhah, A., Fattahi, P., Nouri, B.V. (2015). A hybrid multi-objective genetic algorithm based on the ELECTRE method for a capacitated flexible job shop scheduling problem. *The International Journal of Advanced Manufacturing Technology*, 77(1-4): 51-66.  
<https://doi.org/10.1007/s00170-014-6415-1>