















- [58] Deshmukh, M.P., Sarode, D.D., Chaube A. (2014). Effect of partial replacement of crushed fine aggregates with an industrial waste (red mud) on chloride penetration of concrete. *International Journal of Current Engineering and Technology*, 6(4): 4026-4029.
- [59] Kumar, R. (2014). Study of effect of red mud on the properties of concrete. Diss. National Institute of Technology, Kurukshetra.
- [60] Ribeiro, D.V. (2011). Influência da Temperatura de Calcinação nas Propriedades Cimentícias do Resíduo de Bauxita. Relatório Científico Final de Pós-Doutorado, apresentado à Fundação de Amparo à Pesquisa do Estado de São Paulo (FAPESP). São Carlos, SP, pp. 78.
- [61] Raj Rajendran, R., Perumal Pillaib, E.B., Santhakumai, A.R. (2013). Effective utilization of red mud bauxite waste as a re-placement of cement in concrete for environmental conservation. *Ecology, Environment and Conservation*, 19(1): 247-255.
- [62] Raj, R.R., Pillai, E.P., Santhakumar, A.R. (2012). Strength and corrosion properties of concrete incorporating metakaolin and redmud. *European Journal of Scientific Research*, 91(4): 569-579.
- [63] Zhang, N., Sun, H., Liu, X., Zhang, J. (2009). Early-age characteristics of red mud-coal gangue cementitious material. *Journal of Hazardous Materials*, 167(1-3): 927-932. <https://doi.org/10.1016/j.jhazmat.2009.01.086>
- [64] Wu, C.S., Liu, D.Y. (2012). Mineral phase and physical properties of red mud calcined at different temperatures. *Journal of Nanomaterials*, 2. <https://doi.org/10.1155/2012/628592>