













- with a pyramidal sensor. *Instrumentation Mesure Métrologie*, 16(1-4): 213-228. <https://doi.org/10.3166/im.16.1-4.213-228>
- [3] Ren, Z.H. (2016). Current situation and development trend of ultrasonic nondestructive testing technology. *Technology and Market*, 23(9): 255-256. <http://dx.chinadoi.cn/10.3969/j.issn.1006-8554.2016.09.147>
- [4] Li, Y., Zheng, H., Jia, S.M., Liu, Q., Deng, K., Zhang, J. (2010). Development status of oil and gas pipeline inspection and monitoring technology at home and abroad. *Petroleum Science and Technology Forum*, 31(2): 30-35. <http://dx.chinadoi.cn/10.3969/j.issn.1002-302x.2012.02.007>
- [5] Wang, B. (2018). Design of intelligent inspection robot for oil and gas pipeline defects based on ultrasonic wave. *Modern Computer (Professional Edition)*, (28): 68-70. <http://dx.chinadoi.cn/10.3969/j.issn.1007-1423.2018.28.017>
- [6] Wang, W.M., Wang, X.H., Zhang, S.M., Zeng, M., Wang, H.K. (2014). Long-distance pipeline ultrasonic internal inspection-state of the art. *Oil & Gas Storage and Transportation*, 33(1): 5-9. <http://dx.chinadoi.cn/10.6047/j.issn.1000-8241.2014.01.002>
- [7] Yuan, X.P. (2013). Research and application of the velocity effect of the detector in the magnetic flux leakage pipeline, Shenyang. Shenyang University of Technology.
- [8] Chen, W., Wang, B.L., Wang, B.T. (2018). Application and development of magnetic flux leakage testing technology in pipeline corrosion detection in China. *Petrochemical Technology*, 25(7): 223-330. <http://dx.chinadoi.cn/10.3969/j.issn.1006-0235.2018.07.175>
- [9] Xu, L.L., Wang, J., Jiang, F.R. (2014). Theoretical study on velocity effect of detector in magnetic flux leakage pipeline. *Science & Technology Vision*, (4): 8-14. <http://dx.chinadoi.cn/10.19694/j.cnki.issn2095-2457.2014.04.005>
- [10] Lin, W., Chu, S.N. (2015). Multi sensor data fusion technology for oil pipeline detection. *Journal of Natural Science of Heilongjiang University*, 32(3): 397-403. <http://dx.chinadoi.cn/10.13482/j.issn1001-7011.2015.03.014>
- [11] Zhou, P. (2015). Research and prospect of multi-sensor data fusion technology. *Internet of Things technology*, 5(5): 23-25. <http://dx.chinadoi.cn/10.16667/j.issn.2095-1302.2015.05.037>
- [12] Zhang, S.Q., Zhang, L., Duan, Y. (2003). A data fusion structure based on neural network and D-S inference and its application in ultrasonic testing. *Journal of Sensor Technology*, 16(1): 47-49. <http://dx.chinadoi.cn/10.3969/j.issn.1004-1699.2003.01.012>
- [13] Liao, J.P. (2013). Multisensor data fusion based on D-S evidence theory and artificial neural networks. *Journal of Convergence Information Technology*, 8(8): 1070.
- [14] Yang, D., Ji, H.B., Gao, Y.C. (2018). A robust D-S fusion algorithm for multi-target multi-sensor with higher reliability. *Information Fusion*, 47: 32-44. <https://doi.org/10.1016/j.inffus.2018.06.009>
- [15] Černý, M., Hladik, M. (2018). Possibilistic linear regression with fuzzy data: Tolerance approach with prior information. *Fuzzy Sets and Systems*, 340: 124-144. <http://dx.doi.org/10.1016/j.fss.2017.10.007>
- [16] Baskar, C., Nesakumar, N., Rayappan, J.B.B., Doraipandian, M. (2017). A framework for analysing E-Nose data based on fuzzy set multiple linear regression: Paddy quality assessment. *Sensors and Actuators A: Physical*, 267: 200-209. <https://doi.org/10.1016/j.sna.2017.10.020>